# Electron Accelerator Development Program at BARC

#### ...M.Gantayet & K.C.Mittal

2<sup>nd</sup> International Workshop on Accelerator-driven Subcritical Systems & Thorium Utilization December 12-14, 2011

Bhabha Atomic Research Centre, Mumbai, India

# Outline

1.High power electron linac program in BARC

**2.Technology status** 

3.Project of setting up experimental neutron facility with electron accelerators.

#### **Electron accelerator programme objectives**

- High power electron accelerator programme focused on
- Industrial accelerator for electron irradiation
   X-ray and photoneutron sources
- New and innovative technology solutions
- Build facilities for scientific research and industrial trials
- Diffuse electron accelerator technology in India
- Promote utilisation of electron irradiation in the country
- Economic solution with competitive costs

#### Summary of work of

The high power electron accelerator group of BARC

#### **Electron linac technology development for next 5 years**

10 MeV, 10 kW Linac ( at EBC, Kharghar) Utilization and Upgradation of Facility	2856 MHz	0.9 m
Compact Linac 9 MeV, 6/3 MeV X-Ray source for cargo scanning, research accelerators- productionization at ECIL	2856 MHz	0.9 m and 0.6 m
30 MeV, 7 kW neutron generator for shielding & nuclear physics (n-TOF) studies (IGCAR, Kalpakkam)	2856 MHz	2.5 m
100 MeV, 100 kW neutron generator for ADS and material related studies	2856 MHz	11 m
Superconducting linac	1497/ 1300 MHz	9 cavity cells

### **Electron Beam Utilization of 10 MeV RF Linac**

•Polyethylene o-rings for use up to 250°C

•Reverse recovery time (trr) of Diodes reduced from 15 us to 7µs (BHEL production trials)

•Potato irradiation trials (Food Technology Division, BARC)

•Cross-linking of heat shrinkable rubber (Raychem) •Gelation of Polyvinyl acetate (Pidilite Industries)

• Measurement of Delayed neutron from photofission for Fissile material detection (BARC)

•Photofission data for Mo-99 (BARC)

•Several other research projects of Universities

# **Electron Accelerators as Drivers for ADS**

- **1. Electron accelerator technology is a mature technology**
- 2. Easily used for Bremsstrahlung / photoneutron source
- 3. Isotope production for medical diagnosis and therapy
- 4. Nuclear physics studies related to ADS spallation, higher energy neutron reactions
- 5. Less efficient than proton machines in neutron production but has lower capital cost and comparable energy cost
- 6. ADS application is reliable because of less beam trips
- A thorough evaluation is required for ADS application on a larger scale;
- its suitability for experimental ADS studies is generally accepted.

#### **Electron Beam as a neutron source**

- neutrons are generated via photonuclear and photo fission reactions from Bremsstrahlung photons.
- In the photon energy range from threshold (few MeV) to about 30 MeV, neutron production is via the Giant Dipole Resonance (GDR) mechanism.
- For 5 MW, 100 MeV e- beam, in a dual zone reactor, power increases by 12 times for k=0.98
- Output Power will be ~ 5 x 12 = ~ 60 MW.

Ref:Swanson, IAEA Tech Rep 188 (1979)



Beam Energy (MeV)	Neutron Yeild (n s <sup>-1</sup> kW <sup>-1</sup> )	Beam Current (mA)	Beam Power (MW)	Neutron Flux (n/s)
100 (U – Target)	3.25X10 <sup>12</sup>	50-100	5-10	1.625-3.2X10 <sup>16</sup>
100 (W –Target)	2.17X10 <sup>12</sup>	50-100	5-10	1.085-2.17X10 <sup>16</sup>
100 (Pb – Taget)	1.97X10 <sup>12</sup>	50-100	5-10	0.985-1.97X10 <sup>16</sup>
100 (Ta-Target)	1.91X10 <sup>12</sup>	50-100	5-10	0.955-1.91X10 <sup>16</sup>

# **RF Electron Linac for Neutron Generation**

## PHASE I:

100MeV, 100 kW, pulsed normal conducting Linac (S-band, f = 2856 MHz), avg. neutron flux ~  $10^{13}$  n/cm<sup>2</sup>/s



# **RF Electron Linac for Neutron Generation -2 contd**

#### **PHASE II**

#### 150MeV, 200-300 kW, cw -superconducting Linac (L-band), neutron flux ~ 10<sup>15</sup> n/cm<sup>2</sup>/s



# Main components of 100 MeV/100 kW e-accelerator

1	Electron Gun 1 A / 85 keV	Developed
2	RF Cavities (10 Modules of ~ 10 MeV) (33 Cells, 900 mm long)	Developed
3	Klystrons and Klystron Modulators 10 Nos. Each ( 5 MW peak, 36 kW Av.)	Klystrons development at CEERI, Pilani. Line type modulator developed. Solid State modulator under development
4	Focussing Devices (Solenoid, Quadrupole Magnets)	Experience exists
5	Photo neutron Targets	Design in progress
6	<b>Controls and Instrumentation</b>	Developed for 10 MeV/ 9 MeV/ 6 MeV
7	Super conducting Cavities (Phase – II)	<b>Development in progress</b>

#### **Development of Electron guns**





**Electron gun of 10 MeV Industrial linac** 











**Components of Electron gun** 

#### **Modelling & Simulation of Electron Guns**





Equipotential and Trajectory plot of Planar Geometry Electron Gun

Equipotential and Trajectory plot of Pierce Geometry Electron Gun

# **Gun modulator (line-type)**





#### **Gun modulator of 6 MeV compact linac**



Specifications Voltage : 50 - 100 kVPeak beam current: 0.5 - 1 APulse width :  $5 - 10 \mu \text{s}$ Rep.rate: 10 - 400 Hz

#### **Gun modulator of 10 MeV industrial linac**

# RF Structure - Compact Linac 6/3 MeV (21 Cells)



# **RF** Structure



**10 MeV linac** 





#### 9 MeV linac





X-ray Spot diameter ~ 2.5 mm Measured X-ray dose = 24 Gy/min/m

#### 6/3 MeV linac

# **30 MeV linac Neutron generator RF Measurements on 49 cell and 45 cell Structures**



VNA shows the Electric Field Uniformity along the Accelerator Length

Measured Freq. – 2855.0 MHz,  $Q_0 \sim 10000$  and  $Z_s \sim 80 - 90 \text{ M}\Omega$ 

# **Thermal modelling of 10 MeV Electron Linac**



Contours of Static 1

Contours of Static Temperature (

### **Design tolerances**

#### Achieved during machining of cells

SI.	Parame	Change in frequency
No.	ter	
1.	D	- 34 kHz / μ
2.	В	- 13 kHz / μ
3	L	- 25 kHz / μ
4	Т	+ 25 kHz / μ
5	G	+ 22 kHz / μ
6	α	- 106 kHz / deg.
7	R <sub>in</sub>	- 16 kHz / μ
8	<b>R</b> <sub>on</sub>	- 7 kHz / μ
9	R <sub>ic</sub>	+ 0.1 kHz / μ
10	R <sub>oc</sub>	+ 24 kHz / μ

The RF measurements of Resonant Frequency before and after vacuum brazing has been observed within ~ 0.25 MHz



#### **40 kV Autofocussing Buncher**

- β = 0.66, 0.68, 0.84.
- Autofocussing by electrostatic lens

# <section-header>



#### Schematic of 40 KV Buncher





 $\pi/2$  mode = 2856.4 MHz

#### **Development of Copper Cavity Surface Treatment Process**

#### SURFACE TREATMENT STEPS

- 1. Sample cleaning by ultrasonic in HPLC grade Isopropyl alcohol 10 mins
- 2. DM water (0.75  $\mu$ S)
- 3. Ultrasonic in alkaline soln. pH 9.7 for 10 mins
- 4. DM water rinse
- 5. Acid pickling ~ 5% HCl 5 15 mins
- 6. DM water rinse
- 7. Passivation in CrO3 80g/l and 3cc/l H2SO4 at 523K for 1 min





#### **Evaluation by specular reflection**

- 5% HCI for 6 min pickling shows best surface roughness – Sample S-4
- Passivation did not contribute

Development to achieve surface with low field emission

#### Prototype Dual Energy (6/3 MeV) Compact linac for material discrimination - Assembly & Testing





**X-RAY TARGET** 



6/3 MeV scaled model

#### COLLIMATOR





# Klystron development at CEERI, Pilani



Specifications Frequency : 2856 ± 10 MHz Peak Output Power : 6 MW Avg.Output Power : 24 kW Beam Voltage : 140 – 165 kV Peak beam current: 90-120 A Pulse width : 5 – 10 μs Rep.rate: 10 – 415 Hz

























#### **Klystron modulator development**



Line-type (55 kV, 270 A, 10 μs, 400 Hz) in collaboration with SAMEER, Mumbai



Line-type (150 kV, 110A, 10  $\mu$ s, 400 Hz)

**Normal Conducting** 

- OFHC Copper
- Q ~ 10,000
- Room Temp
- High Power RF
- Electric Field ~ 10 MV/m

Superconducting Niobium Q ~ 10<sup>8</sup> – 10<sup>9</sup> Liquid He Temp. Low power RF 30-40 MV/m

SCRF Leads to Compact Linac Development With additional cost of Cryogenics

#### **Ingot Niobium SCRF Cavity Development**

 $\beta$  = 0.49, f<sub>0</sub> = 1050 MHz large grain niobium cavity electron beam welded.



1.0E+09

0

Parameters	Simulated	Measured
f [MHz]	1036.856	1036.507
Q	17032	8076
Rsh [MΩ/m]	4.711	3.61

RFINPUT SOURCE POWER HAS REACHE MAX.

10

5

E<sub>acc</sub> [MV/m]

Design parameter of the  $\beta$  = 1.0,

f0 = 1050 MHz cavity

Parameter	Value
Cavity diameter	255.4 mm
Cavity length	14.276 mm
Bore radius	43 mm
Accelerating Gradient	25 MV/m

Quench

5

Eacc [MV/m]

β=0.49, f =1050 MHz Niobium Cavity Test Results at 2K (Courtesy: G. R. Myneni, in collaboration with JLab)



1.0E+09 +

# **Neutron Multiplier**





Maximum neutron flux is ~5e12 at Keff of ~0.975 for Tantalum target

# **Target Configuration**

Beam Parameters:
Beam Dia: 30 mm
Beam Energy 100 MeV
Beam power: 100 kW
Duty cycle: 400 Hz
Pulse duration: 10 µs.

Target Geometry:
Rectangular plates (4 cm×4cm)
Number of plates: 11
Thickness: 0.2 – 0.6 cm
Water channel width: 0.2 cm



#### **Schematic of Target configuration**

#### Linear Induction Accelerator (LIA-200) as electron source

# 200keV, 5kA, 50ns, 10-100Hz as a possible injector for linac photoneutron source for nuclear physics experiments





Short Pulse duration (10 – 100 ns)

- High Peak Current (10 50 A)
- ✤ Low Rep Rate ( 10 40 Hz)

# Beam tube delivers the beam from accelerator window to the target vault

- Diameter & divergence of the output beam of 100 MeV accelerator ~ 6mm and 5 mrad resp.
- Sizing of beam tube
- Bending of beam tube through the shielding wall
- Optics for beam expansion
- Beam diagnostics and correction optics
- Minimum loss beam transmission
- Isolation window and linac window design optimization
- Low radiation damage window

# **Main Control loops**

- **1. RF peak power control to set power output**
- 2. Automatic Frequency Control (AFC)
- 3. Phase Control for synchronization between linac stages
- 4. Output current control for beam power output
- 5. Pulse Rep rate depending upon application of linac
- 6. Temperature control for frequency stability

Analog Inputs (AI) /Analog output (AO) ~ 50 Digital Inputs (DI) /Digital outputs (DO) ~ 500 Sensors are developed for most parameters

- **1. Fuel assembly replacement**
- 2. Target replacement and assembly
- 3. Linac window repair and replacement
- 4. Handling of cooling lines of target and neutron multiplier
- 5. Shielding plugs handling
- 6. Handling of contaminated and activated components for replacement
- 7. Manual interventions for maintenance

# **Engineered Safety Aspects**

- 1. Safety of neutron multipliers (Philosophy of reactor safety)
- 2. Neutron & x-ray Radiation shielding & monitoring
- 3. DM Cooling water & interlocks with beam
- 4. Vacuum integrity & interlock with fast closing valves
- 5. Helium cooled isolation windows
- 6. Use of low-activation alloys
- 7. Remote maintenance requirements
- 8. Ozone monitoring & safety
- 9. Safety Stack
- **10.Interlock of steering magnets with beam**
- **11.Interlock of beam expansion optics with beam**
- **12.High power RF and HV safety features**
- **13.Low-level radioactive waste management**

# SUMMARY

High power electron accelerator is a focused program for developing enabling technologies and technology partners Productionisation of the industrial accelerators will help attain technology maturity and develop infrastructure **Development plan for 100 MeV, 100 kW and** 

later cw linac of 250 kW will pave the way for experimental facilities

Engineering design and safety issues are identified

Gratefully acknowledge V. T. Nimje Kavita P. Dixit Jayanta Mandal For inputs in preparing this talk

# Thank you

For

Your kind attention